

Wall Mount Humidity & Temperature Transmitter

Applications:

H1N wall mount temperature and humidity transmitters are designed for environment monitoring and controlling in industrial, commercial and other buildings. These transmitters can be used for indoor air temperature and humidity monitoring in various industrial plant, clean room, lab, machine room, office and commercial building, airport, station, library and stadium, etc.



Features:

- High performance digital sensors and circuits, ensure accurate measurement and temperature compensation
- Good long term stability and reliability
- 100% interchangeable sensors, no re-calibration needed
- Fast response,
- Light and state of art house, easy installation and wiring
- Digital technology applied, multiple output optional, over voltage and reverse polarity protection, high reliability and interference capability

Specifications:

Relative Humidity

Sensor	: Digital polymer
Range	: 0~100%RH
Output	: 4~20mA(2 wires), 0~10VDC(3 wires), RS485
Accuracy	: 1.6% / 2.0% RH (25°C, 20~80%RH)
Hysteresis	: <±1%RH
Response time	: <10s(25°C,in slow air)
Drift	: <±0.5%RH/year

Temperature

Sensor	: Solid state band gap, RTD or thermistor
Range	: 0~50°C, 0~100°C, -40~60°C, or others
Output	: 4~20mA(2 wires), 0~10VDC(3 wires), RS485, RTD or thermistor
Accuracy	: see model table
Power	: Current Output: 7.5~36VDC, Voltage Output: 15~35VAC/DC
Output Load	: <600 Ω (current), >2KΩ (voltage)
Temperature Limit	: -40~100°C, 0~99%RH (Non condensing)
Display	: Large LCD display (Optional)
Display Resolution	: 0.1°C, 0.1%RH
Storage Temperature	: 0~70°C, 0~95%RH (Non condensing)
Housing	: Fireproof ABS
Protection	: IP30

Wall Mount Humidity & Temperature Transmitter

Optional LCD display:

LCD display panel can be ordered and installed in field separately. See details on MMI product.

Optional MMI operation panel:

Including LCD, integrated with function keys, can be ordered and installed in field separately. See details on MMI product

Models:

Code	Descriptions
H1N	: Wall mount Temp./RH transmitter

Code	RH Accuracy
2	: $\pm 1.6\%RH$
3	: $\pm 2.0\%RH$

Code	RH Output (0-100%RH)
1	: 0-10VDC(3 wires)
2	: 4-20mA(2 wires)
8	: RS485, Modbus

Code	Temperature Output
0	: No
1	: 0-10VDC(3 wires) $\pm 0.2^{\circ}C@25^{\circ}C$
2	: 4-20mA(2 wires) $\pm 0.2^{\circ}C@25^{\circ}C$
3	: PT1000, $\pm 0.2^{\circ}C@25^{\circ}C$
4	: PT100, $\pm 0.2^{\circ}C@25^{\circ}C$
5	: NTC20K, $\pm 0.4^{\circ}C@25^{\circ}C$
6	: Ni 1000, $\pm 0.4^{\circ}C@25^{\circ}C$
7	: NTC10K-II, $\pm 0.4^{\circ}C@25^{\circ}C$
8	: RS485, Modbus
9	: NTC10K-III, $\pm 0.4^{\circ}C@25^{\circ}C$
A	: NTC10K-A, $\pm 0.4^{\circ}C@25^{\circ}C$

Code	Temperature Range
0	: No
1	: 0-50 $^{\circ}C$
2	: 0-100 $^{\circ}C$
3	: -40-60 $^{\circ}C$
7	: others

Wall Mount Humidity & Temperature Transmitter

Models:

Code	Relay Contact
0	: No
1	: 2 x SPST (Not Applicable for 4-20mA Output)

Code	LCD Display
0	: No
1	: Yes

Code	Enclosure
-	: Weatherproof Enclosure
Ex	: Explosionproof Enclosure

Dimension (mm):

*H series products are powered on RH circuit, so the RH circuit must be powered. Otherwise it will not work.

