



## Techsense Bangladesh Ltd

## Photoelectric Sensor, Code: CJY18E-05PAT 10-30V DC 3 WIRES

A Photoelectric Sensor consists primarily of an Emitter for emitting light and a Receiver for receiving light. When emitted light is interrupted or reflected by the sensing object, it changes the amount of light that arrives at the Receiver. The Receiver detects this change and converts it to an electrical output. These sensors are made of light sensitive parts. This makes them useful in detecting the light emitters or any type of light source. There are various types of this sensor. Majorly they utilize the phenomena of reflection of light in which emitter and receiver together detect the reflection of light that strikes the object. In some other cases they spot any disturbance due to the target in the beam of light

## **General Attributes**

■ Sensing distance : 5mm

■ Standard sensing target : 18×18× 1mm (Iron)
■ Light source : Infrared LED

■ Response frequency : 500Hz
■ Power supply : 12-24VDC
■ Operating voltage : 10-30VDC
■ Control output : 200mA

■ Insulation resistance : Min. 50MΩ (at 500VD

(megger)

■ Indicator : Operation indicator

(red LED)

■ Ambient temperature : -25~+70°C (No icing)
■ Storage temperature : -30~+80°C (No icing)
■ Ambient humidity : 35~95%RH (No conde-

nsation)

■ Protection circuit : Surge protection circuit,

Over current protection circuit

■ Material : Case/Nut: Nickel plated

Brass, Washer: Nickel plated Iron, Sensing surface

: Heat-resistant ABS

■ Protection : IP67 (IEC, Standard)

## **Application Notes**

Checking presence, inspecting completeness, counting and sorting.

Checking the presence of coloured objects, detection of printed marks, inspecting LEDs, colours andluminescent objects.

Measurement of parts, monitoring of sag, measurement of thickness and distance, measurement of path and filling level.
Reading of bar codes and data matrix codes, OCR, tracking of components, colour identification Front-edge detection, Pick & Place, quality inspection



For further information please visit: https://goo.gl/RGRgkN





LISTED IND. CONT. EQ. 81U2

S for use in the secondary of a class 2 source of supply



