



Techsense Bangladesh Ltd

Photoelectric Sensor, Code: CGY18E-T10PA

A Photoelectric Sensor consists primarily of an Emitter for emitting light and a Receiver for receiving light. When emitted light is interrupted or reflected by the sensing object, it changes the amount of light that arrives at the Receiver. The Receiver detects this change and converts it to an electrical output. These sensors are made of light sensitive parts. This makes them useful in detecting the light emitters or any type of light source. There are various types of this sensor. Majorly they utilize the phenomena of reflection of light in which emitter and receiver together detect the reflection of light that strikes the object. In some other cases they spot any disturbance due to the target in the beam of light

General Attributes

■ Sensing distance : 10m

■ Light source : Infrared LED (880nm)

■ Power supply : 10-30VDC■ Operating voltage : 90-250VAC■ Control output : 200mA

■ Insulation resistance : Min. 50MΩ (at 500VDC

(megger)

■ Indicator : Operation indicator (red LED)

■ Ambient temperature : -15~+55°C
■ Storage temperature : -15~+55°C
■ Ambient humidity : 35~95%RH

■ Protection circuit : Surge protection circuit, Over

current protection circuit

■ Cable : φ4.8, 2P, (AWG24,

Core diameter: 0.1mm, Number of cores: 35,

■ Material : Case/Nut: Plastic, Washer:

Plastic, Sensing surface: PMMA, Standard cable(Gray): Polyvinyl chloride(PVC),Oil resistant cable

(Gray): Oil resistant Polyvinyl

chloride(PVC)

■ Protection : IP67 (IEC, Standard

Application Notes

Checking presence, inspecting completeness, counting and sorting.


Checking the presence of coloured objects, detection of printed marks, inspecting LEDs, colours anduminescent objects.


Measurement of parts, monitoring of sag, measurement of thickness and distance, measurement of path and filling level.

Reading of bar codes and data matrix codes, OCR, tracking of components, colour identification
Front-edge detection, Pick & Place, quality inspection









Wiring Diagram

For further information please visit :https://goo.gl/IV7jBy





LISTED IND. CONT. EQ. 81U2

Solution for use in the secondary of a class 2 source of supply

