

Techsense Bangladesh Ltd

NIETZ INVERTER : NZ2400-30G/37P

NIETZ FREQUENCY INVERTER are compact sensor less vector drive-Overload capacity is 150%(100%) of the rated current, 3s for 180% of the rated current; There are ten auxiliary frequency sources. It can implement fine tuning of auxiliary frequency and frequency synthesis. Two types of control mode: Sensor less flux vector control (VC), V/F (Voltage/Frequency) control.

General Attributes

- Sensing Range
- Power SupplyControl mode
- : 30 kW : 380 V
- : V/F (Voltage / Frequency) Control Sensor less flux vector control (VC)
- Maximum frequency : Vector control: 0–320 H V/F control: 0–3200Hz
 Carrier frequency : 1.0–16.0 kHz
 Input frequency Esolution : Digital setting: 0.01 Hz
 - Analog setting: 0.01 HZ Analog setting: 0.025% of maximum frequency
- Speed range : 1:100 (VC)
 Speed stability accuracy : ± 0.2% (VC)
- Speed stability accuracy
 Torgue control accuracy
- Directe etien mede
- Protection mode
- ± 20%
 Motor short circuit detection at power on, input/
 output phase loss protection, over current protection, overvoltage protection, under voltage protection, overheat protection and overload protection


Application Notes

Machine tools, packaging machine, food equipments, Z pump, fan, elevator, CNC

For further inforZmation please visit : https://goo.gl/vUvD9g



LISTED IND. CONT. EQ. 81U2 US for use in the secondary of a class 2 source of supply





We are the authorized distributor NIETZ of in Bangladesh.