


INDUCTIVE RING AND TUBE SENSOR ,Code : BES03JH

Inductive ring and tube sensors are the perfect solution for the detection of metallic parts in automated feeding systems. These sensors are featured by a high resolution and short response time and will be mainly applied for parts detection and stow control. Inductive ring sensors with dynamic evaluation are featured by an even higher resolution and detect very tiny parts like e.g. springs. The high resolution also stays stable, when the ambient conditions are changing, e. g. metal-containing contamination

General Attributes

- Dimension : 60 x 35 x 20 mm
- Housing style : rectangular
- Housing material : Plastic
- Connection : M12x1-Connector,
: 4-pole, Acoded
- Switching frequency : 16 Hz
- Operating voltage : 10...30 VDC
- Rated operating current : 400 mA
- Rated operating voltage : 24 V
- Ambient temperature : -25...70 °C
- Polarity reversal protected : yes
- Switching output : PNP Normally open
(NO)
- Protection type : IP65
- Approval/Conformity : CE, EAC



Wiring Diagram

Application Notes

Position Detection
Speed Sensing
Limit Switching
Pulse Generation
Distance Measurement
Gear tooth detection for motion monitoring
Valve position control during processing
Foil seal detection inside plastic caps

For further information please visit : <https://goo.gl/E4jh8q>

We are the authorized distributor of balluff in Bangladesh.