

Techsense Bangladesh Ltd

Cam Switch (Multiple-position mechanical), Code : BNS00CT

Mechanical row-position counters with an exchange unit are available for standard applications and for applications with safety switching points. The whole ram unit can be removed using two bolts to replace the individual ram. This saves time and money if service is required because it is not necessary to remove the whole switch. The switches are recognizable by the blue-colored anodized ram plate.

General Attributes


- Dimension : 120 x 80 x 83 mm
- Connection type : 1-3. Switch position: Screw terminal
- Ambient temperature : -5...85 °C
- Approach direction : longitudinal, parallel to attachment surface
- Number of switching positions : 3x Chisel
- Housing material : Aluminum
- Installation : Vertical
- Switch position spacing: 12 mm
- Rated operating voltage Ue : 1-3. Switch position: 250 VAC
- IP rating per IEC 60529: IP67
- Version : Snap contact
- Approval/Conformity : CE, CCC
- Continuous current : 1-3. Switch position: 6 A
- Connection type : 1-3. Switch position: Screw terminal
- Operating principle : 1-3. Switch position: Mechanical
- Approach speed : 1-3. Switch position: 40 m/min

Application Notes

To suit various mounting and fixing methods.
Switch can be directly mounted on back plate for rear mounting
in building control panels and consoles
Cam switches allow control of processes and utilities in industry and buildings and direct control for simple machines.



BSE 30.0



Wiring Diagram

For further information please visit : <https://goo.gl/T2w6jc>

We are the authorized distributor of Balluff in Bangladesh.