

Techsense Bangladesh Ltd

ROTARY PADDLE LEVEL SWITCH Code : SE191B

The purpose of SE series operating principle of the rotary paddle level switch is to detect the presence of solid/powdery material in most kinds of tanks, bins and containers. The unit is usually located through a bin wall at the top, middle or low level of a bin. During normal operation a synchronous motor rotates the paddle at RPM. When this paddle rotation is impeded by material, surrounding the paddle, motor will stall and cause the Micro-switch to change state (indicating an alarm or control). If the rotary paddle bears an extra over load, the motor will be appeared slide to prevent the inside mechanism damaged. The performance of torsion is stable and Reliable

General Attributes

- Power source : 220V AC 50/60Hz
- Contact capacity : SPDT 5A/250VAC
- Operating temperature : - 20~70 deg.c
- Connection : 2-1/2"X5K
- Paddle material : PC ` SUS304
- Process Connection : 2-1/2"*5KG/cm2
- Paddle Shape: scimitar : (100*30)
- Economical type : (Flange)
- Protection class : IP 65

Application Notes

Plastics and synthetics
Chemicals and fertilizer
Pharmaceuticals
Food and beverage,
Agriculture and fodder mills/depots
Cement as well as ceramics
Power plants
Various incinerators



For further information please visit : <https://goo.gl/AAX9uR>

We are the authorized distributor of FINETAK in Bangladesh.

