

SENSOR-SHOPBD.COM
SENSOR-SHOPBD.COM
SENSOR-SHOPBD.COM

Techsense Bangladesh Ltd

NIETZ INVERTER: NZ2200-2R2G

NIETZ FREQUENCY INVERTER are compact sensor less vector drive-Overload capacity is 150%(100%) of the rated current, 3s for 180% of the rated current; There are ten auxiliary frequency sources. It can implement fine tuning of auxiliary frequency and frequency synthesis. Two types of control mode: Sensor less flux vector control (VC), V/F (Voltage/Frequency) control.

General Attributes

■ Power rating : 2.2 KW

■ Power Supply∴ 1PH 220v 50Hz/60Hz∴ Control mode∴ V/F (Voltage / Frequency)

Control

Sensor less flux vector

control (VC)

■ Switching Output : 3PH 220v 10A

■ Maximum frequency : Vector control: 0–320 H

V/F control: 0-3200Hz

■ Carrier frequency :1.0–16.0 kHz

■ Input frequency Esolution : Digital setting: 0.01 Hz

Analog setting: 0.025% of maximum frequency

■ Startup torque : G type: 0.5 Hz/150% (VC ■ Overload capacity : 60s for 150% of the rated

current, 3s for 180% of the ratedcurrent

■ Speed range : 1:100 (VC)
■ Speed stability accuracy : ± 0.2% (VC)

■ Torque control accuracy : ± 20%

■ Protection mode : Motor short circuit detec

tion at power on, input/ output phase loss protection, over current protection, overvoltage protection, under voltage protection, overheat protection and

overload protection

■ Ambient temperature : 10°C ~40°C

■ Humidity : Less than 95%RH,

Application Notes

Machine tools, packaging machine, food equipments, Z pump, fan, elevator, CNC

For further information please visit: https://goo.gl/vUvD9g





LISTED IND. CONT. EQ. 81U2

Solution for use in the secondary of a class 2 source of supply



