

Miniature Circuit Breaker, Code- S201-B32

System pro M compact S200 miniature circuit breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K,Z), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 6 kA at 230/400 V AC) and rated currents (up to 63A). All MCBs of the product range S200 comply with IEC/EN 60898-1, IEC/EN 60947-2, UL1077 and CSA 22.2 No. 235, allowing the use for residential, commercial and industrial applications. Bottom-fitting auxiliary contact can be mounted on S200 to save 50% space.

General Attributes

- Width : 17.5 mm
- Depth : 69 mm
- Height : 88 mm
- Standards : IEC/EN 60898-1
IEC/EN 60947-2
UL 1077
- Rated Current : 32 A
- Rated Frequency : 50 Hz / 60 Hz
- Housing Material : Insulation Group II, RAL 7035
- Contact Position Indication : Red ON / Green OFF
- Operational Voltage : Maximum (Incl. Tolerance) 253 V AC
Maximum (Incl. Tolerance) 72 V DC
Maximum 253 V AC
Maximum 72 V DC
Minimum 12 V AC
Minimum 12 V DC

Application Notes

- ☐
- ☐
- ☐
- ☐



Wiring Diagram

For further information please visit : <https://goo.gl/mjQZHD>

We are the authorized distributor of ABB in Bangladesh.

