

Product Specification of:

## O<sub>2</sub> - Medical Sensor / Type M-10




### :: KEY FEATURE ::

**Gas Sensor that shows high signal stability at low cross interferences to anesthesia gases combined with a superior linearity over the entire range.**

*All characteristics are based on conditions at 25°C, 50% RH and 1013 hPa and gas flow > 2.5 L/min.*

<b>Measurement Range:</b>	0 to 100 Vol.O <sub>2</sub> %
<b>Expected Operating Life:</b>	> 750,000 Vol.% O <sub>2</sub> h
<b>Sensor Lifetime:</b>	> 3 years @ ambient air, depending on application
<b>Electrical Connector:</b>	modular jack 6P4C
<b>Initial Output Signal:</b>	8.0 to 12.0 mV @ dry ambient air
<b>Response Time t<sub>90</sub>:</b>	< 16 s
<b>Drift:</b>	< 1 Vol.O <sub>2</sub> %/month @ air, averaged across 12 months
<b>Operating Temperature:</b>	10 to 40 °C
<b>Static Temperature Error:</b>	< ± 1.5% @ 20-40 °C < - 3% @ 15-20 °C < - 8% @ 10-15 °C
<b>Pressure Range:</b>	650 to 1250 hPa
<b>Linearity Error:</b>	≤ ± 3 % @ 100 Vol.%O <sub>2</sub> , within 5 min
<b>Zero Offset Voltage:</b>	≤ 0.3 Vol% O <sub>2</sub> @ 100 Vol.%N <sub>2</sub> , within 5 min
<b>Repeatability:</b>	± 1 % Vol. O <sub>2</sub> @ 100 Vol.%O <sub>2</sub> , applied for 5 min
<b>Influence of Humidity:</b>	- 0.03 % rel. O <sub>2</sub> reading per % RH
<b>Recommended Load Resistor:</b>	≥ 10 kOhm
<b>Temperature Compensation:</b>	NTC
<b>Interferences:</b>	according to DIN EN ISO 80601-2-55
<b>Weight:</b>	approximately 52 g
<b>Material in Contact with Media:</b>	PA, PPS, PTFE, stainless steel



### :: STORAGE CONDITIONS ::

<b>Temperature Range:</b>	-15 to 50 °C 10 to 30 °C (recommended) 40 to 50 °C (max. for 1 week)
<b>Humidity:</b>	up to 100 % RH, non-condensing
<b>Shelf Life:</b>	< 6 months recommended

### :: RELATED PRODUCTS ::

Product	Part-No.	Housing Colour
O <sub>2</sub> - Sensor M-10	41 00 14	Black
Pck. Unit 50 x M-10	41 04 14	-

*This data sheet is subject to change without prior notice. [M-10\_Rev10-2017\_0215.doc]*

page 1 of 1